

GENEL AMAÇ		KONUTLAR					KONUT DIŐI YAPILAR				
Beyan Yüku (kütle) -kg		HIZ	320	400	630	1000	630	800	1000	1250	1600
KABİN EBATLARI (mm)	GENİŐLİK (CW)		900	1100	1100	1100	1100	1350	1600	1950	1950
	DERİNLİK (CD)		1000	1000	1400	2100	1400	1400	1400	1400	1750
	YÜKSEKLİK(CH)		2200	2200	2200	2200	2200	2200	2300	2300	2300
KABİN ALANI	MİNİMUM (m2)		0,79	0,98	1,45	2,15	1,45	1,73	2,15	2,57	3,24
	MAKSİMUM(m2)		0,9	1,17	1,66	2,4	1,66	2	2,4	2,9	3,56
DURAK KAPILARI	GENİŐLİK (DW)		700	800	800	800	800	800	1100	1100	1100
	YÜKSEKLİK(DH)		2000	2000	2000	2000	2000	2000	2100	2100	2100
KUYU EBATLARI (mm)	GENİŐLİK (SW) Teleskop Kapı		1400	1600	1600	1600	*	*	*	*	*
	GENİŐLİK (SW) Merkez Kapı		*	1800	1800	1800	1800	1900	2400	2600	2600
	DERİNLİK (SD)		1600	1600	1900	2600	2100	2300	2300	2300	2600
KUYU DİBİ DERİNLİĐİ (P), (mm)	0,40 - 0,63		1400	1400	1400	1400	1400	1400	1400	1600	1600
	1		1400	1400	1400	1400	1400	1400	1400	1600	1600
	1,6		*	1600	1600	1600	1600	1600	1600	1600	1600
	2,5		*	*	2200	2200	*	2200	2200	2200	2200
KUYU ÜST BOŐLUĐU (OP), (mm)	0,40 - 0,63		3600	3600	3600	3600	3800	3800	4200	4400	4400
	1		3700	3700	3700	3700	3800	3800	4200	4400	4400
	1,6		3800	3800	3800	3800	4000	4000	4200	4400	4400
	2,5		*	*	5000	5000	*	5000	5200	5400	5400
MAKİNE DAİRESİ	ALAN (L1xL2) m2 Max.	0,63	6	7,5	10	12	15	15	20	22	25
		1	6	7,5	10	12	15	15	20	22	25
		1,6	*	10	12	14	15	15	20	22	25
		2,5	*	*	14	16	*	18	20	22	25
	GENİŐLİK (L1) Min.	0,63	1600	2200	2200	2400	2500	2500	3200	3200	3200
		1	1600	2200	2200	2400	2500	2500	3200	3200	3200
		1,6	*	2200	2200	2400	2500	2500	3200	3200	3200
		2,5	*	*	2800	2800	*	2800	3200	3200	3200
	DERİNLİK (L2) Min.	0,63	3000	3200	3700	4200	3700	3700	4900	4900	5500
		1	3000	3200	3700	4200	3700	3700	4900	4900	5500
		1,6	*	3200	3700	4200	3700	3700	4900	4900	5500
		2,5	*	*	3700	4200	*	4900	4900	4900	5500